

HEAVY DUTY LANOLIN



DESCRIPTION

TREBLEX Heavy Duty Lanolin Aerosol contains pure (USP) pharmaceutical grade lanolin with a safe high purity solvent. Heavy Duty Lanolin Aerosol is a multi purpose natural product designed to lubricate and provide protective coatings to most surfaces. This product is accepted for use in export registered meat establishments.

FEATURES

- 360° Valve
- Bio degradable.
- Non toxic. Biodegrades easily.
- Non carcinogenic.
- Highly resistant to fresh and salt water and salt spray.
- Protects against acids and alkaline corrosive environments.
- Provides self healing film if damaged.
- Safe on all synthetic materials and rubber.
- Natural product contains no petroleum-based compounds.
- Non-evaporative providing long lasting protection.
- Non conductive in electrical applications.

APPLICATIONS

MARINE

- Protection for engines, power generators, tools, manifolds, outboard motors and electrical equipment including marine radio equipment. Provides lubrication for winches, chains, springs and trailer chassis trawling wire in sensitive marine areas.

AUTOMOTIVE

- Automotive protection including battery terminals, ignition systems, latches, rubber belts, springs, hinges, locks, wheels and hubs.

INDUSTRIAL

- Lubricates and penetrates wire ropes, chains, cables and any pivot point on all types of machinery such as Fork Lifts, Cranes, Drag Lines and Conveyor Belts.
- Anti-seizing for nuts bolts and axles.

GENERAL

- Waterproofing and anti-corrosion agent for electrical connections.
- Can be used as a lubricant and protectant in food preparation areas.
- Helps prolong life of rubber seals and o-rings as it is non- perishing.
- Protects all types of machinery, equipment and tools from corrosion, rust and moisture.

DIRECTIONS

- For maximum results always apply to clean dry surface.
- Shake can well before use.
- Spray evenly from approx 20cm to the surface to be treated

SAFETY

Keep out of reach of children. Harmful if swallowed. Use with adequate ventilation. Allow product time to dry before repowering. Read Material Safety Data Sheet before use.

PRODUCT CODE: **THDL**